

UNDERGROUND CAST RESIN MINI SUBSTATION - ENQUIRY FORM

Please Note: RMM's Underground Substations are specifically manufactured to house an SGB transformer.

1. Download and open form with Adobe Acrobat 2. Complete and return via E-mail or Fax

BASIC PERFORMANCE REQUIREMENTS

RATED POWER-kVA:

LOCATION:

TYPE:

SUPPLY SYSTEM DATA

PRIMARY VOLTAGE (V):

SECONDARY VOLTAGE (V):

VOLTAGE MV/LV IS GIVEN BY THE FOLLOWING:

FREQUENCY (Hz):

TAPPING ON HV-SIDE:

CONSTRUCTION DATA

VECTOR GROUP:

NEUTRAL POINT LOADING CAPACITY:

IMPEDANCE (%):

DEGREE OF PROTECTION:

TYPE OF COOLING:

INSULATION CLASS:

WINDING MATERIAL:

ENVIRONMENTAL DATA

ALTITUDE:

AMBIENT TEMPERATURE RANGE (°C):

AIR HUMIDITY (%):

CLIMATIC CONDITIONS:

DUST CONCENTRATION (mg/m3):

TYPE OF DUST (SPECIAL):

ACCESSORIES

HOUSING REQUIRED:

EARTH SWITCHING:

TEMPERATURE SENSOR IN WINDINGS:

COOLING FANS:

CHASSIS WITH ROLLERS:

GENERAL NOTES

PAINT SPECIFICATIONS:

EXISTING DATA SHEET:

EXISTING OUTLINE DRAWINGS:

TESTING:

ADDITIONAL NOTES:

DATE OF ENQUIRY: